

Main

Bezel material	Black plastic
Device short name	SK
Enclosure type	Corrosion resistance enclosure indoor/outdoor Dust and oil resistant weatherproof enclosure indoor/ outdoor
Mounting diameter	1.18 in (30 mm)
Operator additional information	Screw-on plastic mushroom 0.06 in (1.63 mm) Without guard

Complementary

Line Rated Current	10 A
Cap/operator or lens colour	green
Contact operation	Standard fingersafe
Contacts type and composition	1 NC late-break 3 NC
Control type	Illuminated push-button
Electrical connection	Screw clamp terminal
Light block supply	Via transformer 110 V AC 50/60 Hz Via transformer 120 V AC 50/60 Hz
Marking	unmarked
Mounting support	panel
Operator position information	3 positions
Operator profile	1 projecting push-button
Permissible voltage	600 V
Shape	Round head
Type of operator	Maintained Momentary
Utilisation category	DC-13 AC-15

Environment

NEMA Degree of Protection	NEMA 1/2/3/3R/4/4X/6/12/13
Product certifications	UL listed file E42259 CCN NKCR CSA LR24590 class 3211 03 CE

Ordering and shipping details

Category	21429-9001 SK,SKY
Discount Schedule	CS1
GTIN	00785901141839
Package weight(Lbs)	8.00 oz (226.796 g)
Returnability	No
Country of origin	MX

Contractual warranty

Warranty	18 months
----------	-----------